

Mine	Coal Type	Unit size range before loading, mm	Mass, %						Higher Combustion Heat (Qdaf), kcal/kg, Average	Lower Combustion Heat (Qr), kcal/kg, Average	Release of volatile substances (Vdaf), %		Mass, %		Plate Thickness (Y), mm	Hydrogen Content for combustion (Hdaf), %, Average
			Moisture (Wr)		Ash (Ad)		Sulfur (Sd)				Average	Maximum	Minerals	Small Parts		
			Average	Maximu	Average	Maximu	Average	Maximu					Maximum			
A	SSPK	50-300	5.2	7.0	7.9	10.0	0.3	0.5	8350	7100	24.0	26.3		38		4.4
	KSNPK	50-300	5.2	7.0	7.9	10.0	0.3	0.5	8350	7100	24.0	26.3		38	6-7	4.4
	SSOM	13-50	6.0	7.5	8.6	10.5	0.3	0.5	8370	6900	23.5	26.8		25		4.4
	KSNOM	13-50	6.0	7.5	8.6	10.5	0.3	0.5	8370	6900	23.5	26.8		25	6-7	4.4
	SSSH vn / r	0-13	9.5	13.0	21.5	25.0	0.3	0.5	8284	5600	25.0	27.0				4.5
	SSSSheks.	0-13	9.5	10.5	18.2	20.5	0.3	0.5	8300	5900	25.0	27.0				4.5
	SS (2CC, 3CC)	0-300	7.5	10.0	16.0	22.0	0.3	0.5	8300	6200	25.2	27.0	5.0			4.5
	SS (2CC, 3CC)	0-300	7.5	12.0	19.0	25.0	0.3	0.5	8290	6000	25.8	27.0	6.0			4.5
	SSPKO, KSNPKO	25-150	5.2	7.5	10.5	14.0	0.3	0.5	8390	6900	24.5	26.5	2.0	20	6-8	4.5
	SSMSS, KSNMSS	0-25	10.0	13.0	20.6	25.0	0.3	0.5	8290	5680	24.9	27.0			6-8	4.5
B	DR	0-300	12.0	16.0	13.5	18.5	0.2	0.4	7650	5500	44.0	46.5	4.0			5.5
	DR	0-300	14.0	18.0	15.0	20.0	0.4	0.5	7650	5300	44.0	46.5	5.0			5.5
	DPKO (M)	25-300	9.0	11.0	9.0	12.0	0.4	0.5	7730	6000	44.0	46.5	3.0	25		5.5
	HOUSE	0-50	11.5	13.0	11.0	15.0	0.4	0.5	7800	5900	44.0	46.5				5.5
	DPKO	25-300	9.0	11.0	9.0	11.0	0.4	0.5	7800	6000	44.0	46.5		20		5.5
	HOUSE	0-50	12.5	15.5	11.0	14.0	0.4	0.5	7800	5750	44.0	46.5				5.5
	DR	0-300	11.0	13.0	21.5	23.0	0.4	0.5	7750	5100	45.0	46.5	7.0			5.5
	DR	0-300	16.8	21.8	13.4	18.4	0.4	0.6	7440	5100	42.0	43.5	4.0			5.1
	DROCKI	0-300	21.0	25.0	14.0	19.0	0.4	0.6	7200	4400	40.0	40.5	4.0			5.1
	DPKO	25-300	14.4	17.0	10.0	15.0	0.4	0.6	7440	5400	41.9	43.5	2.0	20		5.1
	HOUSE	0-50	16.7	20.0	12.6	17.6	0.4	0.6	7410	5200	41.9	43.5				5.1
	DR mix	0-300	18.0	22.5	13.5	18.5	0.4	0.6	7320	4700	41.5	42.0	4.0			5.1
	DR	0-300	16.5	21.5	13.3	18.3	0.4	0.6	7300	5000	41.8	43.2	4.0			5.4
	DROCK 1	0-300	20.0	25.0	14.4	20.0	0.4	0.6	7000	4300	41.5	42.0	4.0			5.4
	C	SS (3SS)	0-300	7.4	11.0	9.1	14.0	0.4	0.6	8350	6700	21.3	25.0	4.0		
SS (3SS)		0-300	7.4	11.0	20.6	23.7	0.4	0.6	8340	6000	22.0	25.0	4.0			4.5
SSOMSSH		0-50	7.5	11.0	9.0	13.0	0.4	0.6	8350	6700	21.3	25.4	1.0			4.5
SSOMSSH		0-51	7.5	11.0	12.0	15.0	0.4	0.6	8300	6300	21.5	25.4	2.0			4.5
SSPK		50-300	6.0	9.0	5.2	10.0	0.3	0.5	8350	7200	21.3	23.8	4.0	18		4.5
SSOMSSH		0-50	8.0	11.0	8.0	13.0	0.4	0.6	8370	6900	21.3	23.8				4.5
SSPK		50-300	7.0	10.0	4.5	7.5	0.4	0.6	8400	7250	20.0	23.8		15		4.5
SSOM		13-50	7.0	10.0	4.5	7.5	0.4	0.6	8400	7250	20.0	23.5		25		4.5
SSSS		0-13	10.0	12.0	9.0	12.5	0.4	0.6	8350	6600	21.5	23.5				4.5
SSSS		0-13	10.0	12.0	16.0	20.0	0.4	0.6	8350	6200	23.5	25.0				4.5
SSOMSSH		0-50	9.0	11.0	8.0	12.5	0.4	0.6	8380	6800	21.3	23.0				4.5
SSOMSSH		0-50	8.5	12.0	13.0	16.0	0.4	0.6	8350	6300	23.5	25.4				4.5
SSPKO		25-200	5.0	8.5	6.0	9.0	0.3	0.5	8400	7200	22.6	25.0		20		4.5
KOR		0-300	6.0	9.0	23.5	26.5	0.4	0.7	8200	5700	26.8	28.0			10	4.9
KOR		0-300	6.0	9.0	25.0	28.0	0.4	0.7	8200	5600	25.0	28.0			10	4.9
DAC		0-300	6.0	9.0	22.5	25.5	0.4	0.7	8200	5800	23.8	25.0			8	4.9
KO con-t		0-100	9.0	9.5	8.5	9.5	0.4	0.7	8470	6900	25.0	27.0			10	4.9
Cop con		0-100	9.0	9.5	8.5	9.5	0.4	0.7	8470	6900	23.8	24.5			8	4.9

D	TOMSSH	0-50	6.7	9.0	19.0	24.0	0.4	0.5	8360	6100	14.0	17.0	4.0			3.5
	TOMSSH	0-50	6.7	9.0	12.0	14.0	0.4	0.5	8400	6600	14.0	17.0	1.0			3.5
	TOMSSH	0-50	6.7	9.0	17.3	19.0	0.4	0.5	8400	6300	14.0	17.0	2.0			3.5
	TPKO, TPKOM	13-300	5.7	8.0	20.0	25.0	0.4	0.6	8400	6000	14.5	17.0	8.0	25		3.5
	TR	0-300	6.7	10.0	20.0	25.0	0.4	0.6	8380	5900	14.0	17.0	5.0			3.5
	SSPKO	25-200	6.0	9.0	7.0	10.0	0.4	0.6	8450	7000	22.0	25.0	1.0	20		4.5
	SSMSSH	0-25	8.5	12.0	14.0	18.0	0.4	0.6	8400	6400	20.0	25.0				4.5
	SS3SS	0-300	6.7	10.0	14.5	18.0	0.4	0.6	8400	6300	24.0	27.0	4.0			4.5
	SSPKO, SSPK	25-300	5.6	9.0	15.0	18.0	0.4	0.6	8430	6200	23.2	25.0	5.0	20		4.5
	SSOMSSH	0-50	6.7	9.0	13.0	15.4	0.4	0.6	8400	6300	24.0	27.0				4.5
	DURATION 1	0-300	16.0	18.0	20.0	22.0	0.4	0.7	7600	4800	27.0	29.0	4.0			4.5
	DAC	0-300	6.7	9.0	20.0	22.0	0.4	0.7	8400	6000	26.0	27.0	4.0		8	4.7
	KOR	0-300	6.7	9.0	20.0	22.0	0.4	0.7	8400	6000	27.0	29.0	4.0		10	4.7
	KC con-t	0-100	8.0	9.5	7.5	9.0	0.4	0.7	8450	6900	26.0	27.0			8	4.7
	KO con-t	0-100	8.0	9.5	7.5	9.0	0.4	0.7	8450	6900	27.0	29.0			10	4.7
	SSOMSSH with OF	0-100	8.0	9.5	7.5	9.0	0.4	0.6	8450	6900	24.0	26.0				4.5
	T con	0-100	8.0	9.5	7.5	9.0	0.4	0.6	8450	6900	11.5	14.0				3.5
	SSPK	50-300	8.0	9.0	4.9	6.0	0.4	0.5	8180	6900	29.5	33.3	1.0	15		4.5
	MTR	25-50	8.2	10.0	6.7	8.0	0.4	0.5	8160	6730	30.0	34.4	2.0	18		4.5
	SSPKO	25-200	9.0	11.0	9.8	14.0	0.4	0.5	8150	6420	32.0	34.8	2.0	18		4.5
SS (2CC, 1CC)	0-300	9.0	12.0	8.1	11.0	0.4	0.6	8120	6530	31.0	34.0	2.0			4.5	
SSOMSSH	0-50	10.5	11.0	12.5	14.0	0.4	0.6	8120	6150	31.5	35.5	1.0			4.6	
SSOMSSH	0-50	10.5	11.0	16.5	20.0	0.4	0.6	8120	5830	32.0	35.5	2.0			4.6	
SSOMSSH	0-50	10.5	13.0	20.0	25.0	0.4	0.6	8000	5500	33.0	36.0	4.0			4.6	
E	DG power	0-300	12.5	14.0	16.0	20.0	0.5	0.7	7850	5500	38.5	41.5	4.0		7	5.4
	DGOKI	0-300	15.0	18.0	17.0	22.0	0.4	0.6	7400	5000	39.5	42.0	4.0			5.4
	DGOKII	0-300	24.0	27.0	19.0	23.5	0.4	0.6	6700	3800	40.0	42.0	4.0			5.4
	DG kombyt.	0-300	11.0	13.0	14.0	18.0	0.5	0.7	7900	5750	38.5	41.7	4.0		7	5.4
	DGPKO	25-200(300)	8.5	11.0	14.0	18.0	0.6	0.8	8000	6000	38.5	41.7	4.0	20	7	5.4
	DGOMSSH	0-50	10.0	12.0	12.5	15.9	0.6	0.9	8000	6000	38.5	41.7	2.0		7	5.4
	GR	0-300	8.5	12.5	16.5	18.0	0.5	0.6	8000	6030	40.0	41.0	3.0		9	5.1
	GR	0-300	10.0	12.5	22.5	25.0	0.5	0.6	7900-7700	5300	40.0	41.0	6.0		9	5.1
	GROKI	0-300	15.5	17.5	20.5	25.0	0.5	0.6	7350-6930	4700	39.0	40.0	3.5			5.1
	GROCII II	0-300	22.0	27.0	20.5	25.0	0.5	0.6	6800	4000	39.0	40.0	3.5			5.1
	GOMSSH	0-50	10.0	11.0	14.5	17.0	0.5	0.6	8000	6200	40.0	41.1	2.0		10	5.2
	DR	0-300	12.4	15.0	15.5	20.0	0.4	0.6	7600	5400	40.5	42.0	3.0			5.4
	DROCKI	0-300	17.0	22.0	16.5	20.0	0.4	0.6	7300	4750	40.5	42.0	3.0			5.4
	DPKO	25-200(300)	12.0	14.0	13.0	15.0	0.4	0.6	7700	5500	40.5	42.0	2.0			5.4
	HOUSE	0-50	12.5	14.0	15.5	20.0	0.4	0.6	7700	5500	40.5	42.0	2.0			5.4
	DGR	0-300	11.0	13.0	15.5	20.0	0.4	0.6	7780	5700	40.0	42.7	3.0			5.4
	DGOMSSH	0-50	11.0	13.0	12.2	15.0	0.4	0.6	7850	5900	39.9	42.7	2.0		6	5.4
DGR	25-100	12.0	14.5	12.3	15.0	0.4	0.6	7750	5750	39.5	42.0	2.0			5.4	
DGOMSSH	0-50	13.0	15.0	12.5	15.0	0.4	0.6	7700	5600	39.5	42.0	2.0			5.4	
F	TR	0-300	7.5	10.0	19.5	24.0	0.5	0.8	8410	6150	15.0	17.0	5.0			3.9
	TROCI	0-300	13.5	15.0	22.7	25.0	0.4	0.8	7650	4950	19.0	20.0	3.0			3.9
	TR	0-300	5.5	8.0	15.5	20.0	0.4	0.8	8460	6550	13.5	15.0				3.9
	TOMSSH	0-50	7.5	10.0	17.5	19.0	0.4	0.8	8420	6260	13.5	17.0	1.0			3.9
	TOMSH -1	0-50	7.0	9.0	9.5	10.5	0.4	0.6	8480	6900	14.0	16.0				3.9
	TOMSH -2	0-50	8.0	10.0	19.0	24.0	0.4	0.6	8000	5760	14.5	16.0				3.9
	TR	0-300	7.5	10.0	19.5	23.0	0.5	0.8	8380	6000	16.6	19.0	3.0			4
	TROCI	0-300	15.0	16.0	22.0	25.0	0.5	0.8	7500	4750	23.0	24.0	3.0			4
	TPOKII	0-300	16.5	21.0	23.0	25.0	0.5	0.8	6950	4280	27.0		3.0			4
	KCP(TCP)	0-300	7.0	10.0	17.5	21.0	0.4	0.6	8380	6200	17.7		3.0		6-8	4